


Series 04 E-Chain® - non snap-open

Part No.	B_i [mm]	B_a [mm]	R [mm]	Bending radii					Weight [kg/m]
04.07. <input type="text"/> .0	7	12	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	≈ 0,07
04.10. <input type="text"/> .0	10	15	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	≈ 0,08
04.16. <input type="text"/> .0	16	21	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	≈ 0,09
04.20. <input type="text"/> .0	20	25	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	≈ 0,10
04.30. <input type="text"/> .0	30	35	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	≈ 0,11

Supplement Part No. with required radius. Example: 04.07. .0

0 = standard color, other colors ► page 1.39 · Pitch = 16,7 mm/link - Links/m = 60

Part No. structure



Phone +49- (0) 22 03-96 49-800
Fax +49- (0) 22 03-96 49-222

igus® GmbH
51147 Cologne

Internet: www.igus.eu
E-mail: info@igus.de