

Sensors for direct connection

CMC III smoke detector

Optical component monitors the room air for smoke particles.

Connection:

- 2 x RJ 45: CAN bus

Material:

- Plastic

Colour:

- White

Supply includes:

- Mounting bracket
- Assembly parts

Packs of	PU Compact	PU	Model No.
	Max. no. of		
1 pc(s).	4	32	7030.400

! Also required:

- CMC III Processing Unit/Compact 7030.000/7030.010, see Catalogue 34, from page 450

Available from November 2014



CMC III leakage sensor

Monitors a given point on the floor of the data centre or enclosure for liquids. The external sensor probe allows free selection of the point to be monitored.

Connection:

- 2 x RJ 45: CAN bus

Material:

- Plastic

Colour:

- Front and sensor head: RAL 9005
- Enclosure: RAL 7035

Supply includes:

- Sensor with connection cable, 3 m
- Mounting bracket
- Assembly parts

Packs of	PU Compact	PU	Model No.
	Max. no. of		
1 pc(s).	4	32	7030.430

! Also required:

- CMC III Processing Unit/Compact 7030.000/7030.010, see Catalogue 34, from page 450

Available from November 2014



CMC III leakage sensor, 15 m

Monitors a larger floor area for liquids using the 15 metre long detection cable. The sensor additionally indicates the section of cable where a leak has been detected.

Connection:

- 2 x RJ 45: CAN bus

Material:

- Plastic

Colour:

- Front and detector cable: RAL 9005
- Enclosure: RAL 7035

Supply includes:

- Detector cable, 15 m
- Mounting bracket
- Assembly parts

Packs of	PU Compact	PU	Model No.
	Max. no. of		
1 pc(s).	4	32	7030.440

! Also required:

- CMC III Processing Unit/Compact 7030.000/7030.010, see Catalogue 34, from page 450

Available from November 2014

