


# System accessories AX

## Door installation



### Support strips

#### for door installation, for AX

For attachment of

- Cable ducts
- Cable conduit holders
- Equipment installed on the door
- Cable clamping and attachment

4.5 mm diameter hole on a 25 mm DIN pitch pattern

#### Installation options:

- In the AX enclosure door with cam lock

#### Material:

- Sheet steel

#### Surface finish:

- Zinc-plated

#### Supply includes:

- Assembly parts

For door width mm	Length mm	Packs of	Model No.
380	320	20 pc(s).	<b>4599.100</b>
400	340	20 pc(s).	<b>4694.000</b>
500	440	20 pc(s).	<b>4695.000</b>
600	540	20 pc(s).	<b>4696.000</b>
760	700	20 pc(s).	<b>4599.200</b>
800	740	20 pc(s).	<b>4697.000</b>



#### Also required:

- For installation in AX stainless steel: AX perforated door strip, stainless steel, see page 70



#### Accessories:

- Screws and self-tapping screws M5, see page 81

### Punched section with mounting flange, 14 x 39 mm

#### for door installation, for AX

For the attachment of

- Cable ducts
- Cable conduit holders
- Equipment installed on the door, etc.

#### Installation options:

- In the AX enclosure door with locking rod

#### Material:

- Sheet steel

#### Surface finish:

- Zinc-plated

#### Supply includes:

- Assembly parts

For door width mm	Distance between attachment points mm	Packs of	Model No.
600	475	4 pc(s).	<b>8619.720</b>
800	675	4 pc(s).	<b>8619.730</b>
1000	375	4 pc(s).	<b>8619.710</b>
1200	475	4 pc(s).	<b>8619.720</b>



#### Also required:

- For installation in AX stainless steel: AX perforated door strip, stainless steel, see page 70



#### Accessories:

- Screws and self-tapping screws M5 for configuring the customer's own components on the punched section with mounting flange, see page 81

### Perforated door strip

#### for AX stainless steel

For vertical mounting on the threaded bolts of the door.

For attachment of

- Support strips
- Punched section with mounting flange, 14 x 39 mm
- Door stay

#### Material:

- Sheet steel

#### Surface finish:

- Zinc-plated

For door height mm	Packs of	Model No.
760	2 pc(s).	<b>2311.076</b>
1000	2 pc(s).	<b>2311.100</b>
1200	2 pc(s).	<b>2311.120</b>



#### Accessories:

- Support strips, see page 70
- Punched section with mounting flange, 14 x 39 mm, see page 70
- Door stay, see page 71
- Screws, see page 81